

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Naoaki KODAIRA et al.

Title: IMAGE PROCESSING
APPARATUS, IMAGE FORMING
APPARATUS, AND IMAGE
PROCESSING METHOD
DEPENDING ON THE TYPE OF
ORIGINAL IMAGE

Appl. No.: Unknown

Filing Date: March 17, 2000

Examiner: Unknown

Art Unit: Unknown

UTILITY PATENT APPLICATION
TRANSMITTAL

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. § 1.53(b) is the nonprovisional utility patent application of:

Naoaki KODAIRA
Hiroaki KUBOTA
Hiroki KANNO

Enclosed are:

- [X] Specification, Claim(s), and Abstract (78 pages).
- [X] Formal drawings (28 sheets, Figures 1-36).
- [X] Unexecuted Declaration and Power of Attorney (4 pages).
- [X] Claim for Convention Priority and certified copies of priority documents.
- [X] Information Disclosure Statement.
- [X] Form PTO-1449 with copies of 1 listed reference(s).



The filing fee is calculated below:


	Claims as Filed	Included in Basic Fee	Extra Claims	Rate	Fee Totals
Basic Fee				\$690.00	\$690.00
Total Claims:	41	- 20	= 21	x \$18.00	= \$378.00
Independents:	3	- 3	= 0	x \$78.00	= \$0.00
If any Multiple Dependent Claim(s) present:			+	\$260.00	= \$0.00
				SUBTOTAL:	= \$1068.00
[] Small Entity Fees Apply (subtract 1/2 of above):				=	\$0.00
				TOTAL FILING FEE:	= \$1068.00

- [] A check in the amount of \$1068.00 to cover the filing fee is enclosed.
- [X] The required filing fees are not enclosed but will be submitted in response to the Notice to File Missing Parts of Application.
- [] The Assistant Commissioner is hereby authorized to charge any additional fees which may be required regarding this application under 37 C.F.R. §§ 1.16-1.17, or credit any overpayment, to Deposit Account No. 19-0741. Should no proper payment be enclosed herewith, as by a check being in the wrong amount, unsigned, post-dated, otherwise improper or informal or even entirely missing, the Assistant Commissioner is authorized to charge the unpaid amount to Deposit Account No. 19-0741.

Please direct all correspondence to the undersigned attorney or agent at the address indicated below.

Respectfully submitted,

Date: March 17, 2000

By 

FOLEY & LARDNER
Washington Harbour
3000 K Street, N.W., Suite 500
P.O. Box 25696
Washington, D.C. 20007-8696
Telephone: (202) 672-5300
Facsimile: (202) 672-5399

Richard L. Schwaab
Attorney for Applicant
Registration No. 25,479

TITLE OF THE INVENTION

IMAGE PROCESSING APPARATUS, IMAGE FORMING APPARATUS,
AND IMAGE PROCESSING METHOD DEPENDING ON THE TYPE OF
ORIGINAL IMAGE

5 CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Applications No. 11-094981, filed April 1, 1999; and
10 No. 11-094982, filed April 1, 1999, the entire contents
of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to an image
processing apparatus, an image forming apparatus, and
an image processing method for performing a specified
15 conversion process when filing or copying documents or
images.

In an image forming apparatus, color or
monochromatic images of color or monochromatic copier
or the like are read, and copy images are formed, and
20 when copying, a high image quality is required
regardless of the type of the original image.

The image quality of the image information
necessary to realize a high copy image quality differs
significantly depending on the type of the original to
25 be copied. For example, in the case of a photographic
original, reproduction of color and gradation is
important, and the image quality true to the original

is demanded. On the other hand, in the case of a document original mainly containing characters, the clarity is demanded rather than the color of characters, and an easy-to-read image quality is required.

5 In a conventional copier, however, original modes optimizing the quality of copy image in various originals are available (character/photo mode, character mode, photo mode, map mode and the like), and the user selects a proper original mode depending on
10 the type of the original to be copied, and copies the image. Herein, the character mode and photo mode are exclusive modes for character only and photo only, and in the case of a mixed original of character and photo, the character/photo mode is used. For example, this
15 sort of the image forming apparatus is disclosed in US patent application No. 08/682,007, in which the image processing apparatus can extinguish character area, a graph area, page area, and photo area from the image data, and it processes the image data corresponding to
20 the extinguished areas.

 However, discrimination of regions conducted by the apparatus is not always perfect in precision of discrimination, and wrong discrimination may occur, and therefore depending on the condition of image
25 processing, the image quality may deteriorate extremely in a falsely discriminated region, or when regions of same type are discriminated differently, the image

quality differs in the boundary of the two regions. To decrease problems due to such wrong discrimination, the difference in processing is reduced between the image types to be discriminated, and in the case of wrong discrimination, deterioration of image quality due to wrong discrimination may be made less obvious, but when the difference in processing between plural image types to be discriminated is reduced, the degree of improvement of image quality when discriminated correctly is smaller, and therefore the image quality when the original of characters only is, for example, formed in character/photo mode is inferior to the case when formed in character mode if discriminated correctly. Hence, more accurate discriminating capability of image types of original is demanded, and the image processing apparatus capable of processing the image accordingly is required.

BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to present an image processing apparatus, an image forming apparatus, and an image processing method capable of discriminating the types of original images correctly, and processing the images most efficiently suited to the type of the original image.

The present invention provides an image processing apparatus comprising input means for inputting image data of an original image; discriminating means for

extracting a predetermined region by using a feature of pixel of the image data input from the input means, and for discriminating the attribute of the region; determining means for determining the type of the image data on the basis of the distribution of the regions attribute of which discriminated by the discriminating means; and processing means for processing the image data as specified depending on the type of the image data determined by the determining means.

10 With such constitution, the present invention discriminates attributes of image types in plural regions, and determines the image type of the entire document image on the basis of the distribution of the discriminated attributes. As a result, the image types can be determined more accurately, and correct processing is done securely depending on the image type of the document, so that an image processing apparatus capable of obtaining image data with high image quality can be presented.

20 The present invention further provides an image forming apparatus comprising input means for inputting image data of an original image; discriminating means for extracting a predetermined region by using a feature of pixel of the image data input from the input means, and for discriminating the attribute of the region; determining means for determining the type of the image data on the basis of the distribution of the

25

regions attribute of which discriminated by the
discriminating means; processing means for processing
the image data as specified depending on the type of
the image data determined by the determining means; and
5 image forming means for forming an image on a recording
medium on the basis of the image data processed as
specified by the processing means.

In the present invention, as described above, in
the image processing apparatus and image forming
10 apparatus, optimum image processing is done depending
on the type of the document image by the same principle
of operation, so that image data and image are formed
at high image quality.

Additional objects and advantages of the invention
15 will be set forth in the description which follows, and
in part will be obvious from the description, or may be
learned by practice of the invention. The objects and
advantages of the invention may be realized and
obtained by means of the instrumentalities and
20 combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated
in and constitute a part of the specification,
illustrate presently preferred embodiments of the
25 invention, and together with the general description
given above and the detailed description of the
preferred embodiments given below, serve to explain the

principles of the invention.

FIG. 1 is a block diagram showing a schematic constitution of an image processing apparatus in a first embodiment of the present invention;

5 FIG. 2 is a flowchart for explaining an example of image processing in the image processing apparatus in the first embodiment;

10 FIG. 3 is a flowchart for explaining the image type determining process in the image processing apparatus in the first embodiment;

FIG. 4 is a flowchart for explaining the image type determining process in the image processing apparatus in the first embodiment;

15 FIG. 5 is a flowchart for explaining the data converting process in the image processing apparatus in the first embodiment;

FIG. 6 is a block diagram showing a schematic constitution of an image processing apparatus in a second embodiment of the present invention;

20 FIG. 7 is a flowchart for explaining an example of image processing in the image processing apparatus in the second embodiment;

25 FIG. 8 is a flowchart for explaining the image correcting process in the image processing apparatus in the second embodiment;

FIG. 9 is a block diagram showing a schematic constitution of an image processing apparatus in a

third embodiment of the present invention;

FIG. 10 is a flowchart for explaining an example of image processing in the image processing apparatus in the third embodiment;

5 FIG. 11 is a flowchart for explaining the image type changing process in the image processing apparatus in the third embodiment;

10 FIG. 12 is a block diagram showing a schematic constitution of an image processing apparatus in a fourth embodiment of the present invention;

FIG. 13 is a flowchart for explaining an example of image processing in the image processing apparatus in the fourth embodiment;

15 FIG. 14 is a flowchart for explaining the application starting process in the image processing apparatus in the fourth embodiment;

FIG. 15 is a block diagram showing a schematic constitution of an image forming apparatus in a fifth embodiment of the present invention;

20 FIG. 16 is a diagram showing an example of constitution of image processing means;

FIG. 17 is a diagram showing an example of circuit constitution of color converting means;

25 FIG. 18 is a diagram showing an example of circuit constitution of space filter means;

FIG. 19 is a diagram showing a filter constitution;

FIG. 20 is a diagram showing a specific example of circuit constitution of space filter means;

FIG. 21 is a diagram showing an example of circuit constitution of black printing means;

5 FIG. 22 is a diagram showing an example of constitution of γ -correcting means;

FIG. 23 is a diagram for explaining setting of density converting curve;

10 FIG. 24 is a diagram showing constitution of binary processing by error diffusion method;

FIGS. 25A, 25B are diagrams for explaining gradation processing means;

FIG. 26 is a diagram showing an example of constitution of page information discriminating means;

15 FIG. 27 is a diagram showing an example of constitution of image forming apparatus when using page discriminating information and rectangle discriminating information according to a sixth embodiment;

20 FIGS. 28A to 28D are diagrams for explaining page discriminating information and original mode;

FIG. 29 is a diagram showing an example of constitution of image processing means for executing image processing by discriminating in pixel unit according to a seventh embodiment;

25 FIG. 30 is a diagram showing an example of circuit constitution of pixel unit discriminating means;

FIG. 31 is a diagram for explaining a window of

4×4;

FIG. 32 is a diagram showing an example of constitution of image forming apparatus when using page discriminating information by pixel unit discriminating means according to an eighth embodiment;

FIG. 33 is a diagram showing an example of constitution of image forming apparatus when becoming impossible to discriminate according to a tenth embodiment;

FIG. 34 is a diagram showing an example of constitution of image forming apparatus when becoming impossible to discriminate according to an eleventh embodiment;

FIG. 35 is a diagram showing other example of constitution of image forming apparatus when using page discriminating information according to a twelfth embodiment; and

FIG. 36 is a diagram showing the relation of original mode expressing the operation mode, page discriminating information, and processing condition of each image processing block.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, embodiments of the present invention are described in detail below.

<First Embodiment>

A first embodiment of the present invention is described below. FIG. 1 shows a schematic constitution

of an image processing apparatus according to the first embodiment of the present invention. In FIG. 1, the image processing apparatus comprises an image input unit 101, a region discriminating unit 102, an image type determining unit 103, a data converting unit 104, and an image forming unit 105.

The image input unit 101 is a device for inputting image data, and by an image input device such as image scanner or a device for reading a document and converting into image data, this is a device for incorporating what is depicted from document or other paper. The image input unit of the present invention may be composed of a reading device such as image scanner, or a device for incorporating image already stored in a filing device or the like as image data.

The region discriminating unit 102 is to discriminate a pixel having character as a region from the image data input from the image input unit 101. First, the image data input in the image input unit 101 is separated into a plurality of binary image data depending on the density difference of peripheral pixels, chroma and other state, and divided and extracted into each region where the character or pattern is coupled physically or logically from the image, and feature quantities such as the position of the reason, its size, shape, structure and density distribution are measured, and the attribute is

determined as the document element. Attribute types of document elements include character, photograph, drawing, table, and dots.

5 Some specific techniques for separating into a plurality of binary image data can be used. In this case, as the output of the image separating unit 102, seven pieces of binary separate image data are created, that is, character image, half tone image, background image, dot image, color image, gray image, and black
10 image. These techniques are already known.

Some specific techniques for extracting and for discriminating documents elements may be used.

15 In the region discriminating region 102, not only from single image data, feature quantities of a plurality of image data are integrated according to a rule, and the region attribute of the input image data is determined. For example, from both character image and half tone image, when regions are extracted at the same position, the type of the region and the size of
20 the region are determined. For example, when a photo region is present on the character image, and a half tone image and a half tone pixel are present at a same position, it is determined as a continuous gradation photo region. Some specific techniques for determining
25 the region attribute from plural pieces of image data are already known, and may be used.

The image type determining unit 103, of which

detail is described below, determines feature quantities such as presence or absence of key regions such as dot and photograph, and complicatedness as document structure depending on the degree of overlapping of rectangular regions, from the results discriminated in each region such as character, photograph, drawing, table and dot in the region discriminating unit 102, and determines what kind of document is the input image data.

10 Herein, types of image data include, for example:

1) The background is uniform, and only characters, drawings and tables are present.

2) The background has dots, and only characters, drawings and tables are present.

15 3) Only dot photograph is present.

4) Only continuous photograph is present.

5) At least one of characters, drawings and tables coexists with dot photograph, and also it is possible to extract a rectangular region; or at least one of characters, drawings and tables coexists with continuous photograph, and also it is possible to extract a rectangular region.

20 6) At least one of characters, drawings and tables coexists with dot photograph, and it is impossible to extract a rectangular region; or at least one of characters, drawings and tables coexists with continuous photograph, and it is impossible to extract

a rectangular region.

The data converting unit 104, of which detail is described later, changes the type of input image data according to the type of the document corresponding to the type of image determined in the image type determining unit 103. Change of type of image data may be, for example, change of resolution, compression rate, or number of colors. Also, the region information of attribute may be converted into an image.

The image forming unit 105 is to form an image of image data converted by the data converting unit 104 on a recording medium such as a sheet. At this time, further, it may be also saved in a storage as image file.

In such constitution, processing of the image processing apparatus of the present invention is described below.

FIG. 2 is a flowchart showing an example of document processing procedure in the image processing apparatus shown in FIG. 1. Referring to this flowchart, flow of processing of the image processing apparatus of the present invention is described below.

First, a document image is taken into the image input unit 101 (step ST201). That is, using an image input device such as scanner, the image is read from the documents, or a filing system or the like containing image file data is converted into image data

by the image input unit 101.

In the region discriminating region 102, reading out one line or several lines from the image input device, data is divided into a plurality of binary image data depending on the state of each pixel such as density difference of peripheral pixel or chroma, and divided and extracted in each region in which the character or pattern is coupled physically or logically, and the type of region and degree of importance are discriminated by measuring the feature quantities such as the position of the region, its size, shape, structure and density distribution, thereby extracting character, photograph, drawing, table and dot regions (step ST202). This operation is repeated until processing of all pixels of the input image is over (step ST203).

After all pixel attributes are determined, in the image type determining unit 103, from the results discriminated in each region of character, photograph, drawing, table and dot, by determining the feature quantities such as presence or absence of key regions such as dot and photograph, and complicatedness as document structure from the degree of overlapping of rectangular regions, it is determined what kind of document is the input image data (step ST204). The detail of specific processing in the image type determining unit 103 is described later by referring to

FIG. 3.

After determining the type of the document of the input image data, in the data converting unit 104, the format of image data is converted depending on the document type according to the type of the image data (step ST205). The detail of specific processing in the data converting unit 104 is described later by referring to FIG. 5.

Finally, in the image forming unit 105, the image converted in the image data format is formed on a recording medium (step ST206).

This is a rough processing operation of the image forming apparatus. The processing of individual elements is described specifically below.

FIG. 3 is a flowchart showing the detail of image type determining process as an example in the image type determining unit 103 of the image processing apparatus, and this is a flowchart of the process corresponding to step ST204 shown in FIG. 2. The image type determining process is a process of what kind of document is the input image data, by making use of the region discriminating result of each pixel.

In this process, first, an example of document type classification determined by the type of image data is described below.

A uniform background original document is one not having photo region and dot region. It is therefore an

original of character region only or in a blank state in which nothing is written.

5 A dot background original is one having a dot region, and having a character region contained in the dot region.

A dot photo original is one having a dot region, and having photo region in the dot region but not having character region.

10 A continuous gradation photo original is one not having dot region and character region, and having photo region only.

15 A rectangular discrimination original does not belong to any one of uniform background original, dot background original, dot photo original, or continuous gradation photo original, and not having complicated layout structure, which can be divided into each region of character, dot, photograph, drawing, table, etc.

20 One having complicated layout structure, which cannot be divided into each region of character, dot, photograph, drawing, table and the like, is discriminated from other originals as an indiscriminative original.

25 In FIG. 3, pixel attribute data 151 is the attribute of each pixel of input image data determined by using the type and importance of the region of the plural image data discriminated in the region discriminating unit 102, and is expressed as the region

of each document element.

First, reading data from the pixel attribute data 151, it is checked if dot region is present or not (step ST301). If a dot region is present, then it is
5 checked if photo region is present or not (step ST302). If a photo region is present, then it is checked if character region is present or not (step ST303). If a character region is present, it is a rectangle discrimination candidate original 152. The rectangle
10 discrimination candidate original 152 is classified into rectangular discriminative original or indiscriminative original, consequently by the process for verification of complicatedness of the layout structure. A detailed description of this process is
15 given later by referring to FIG. 4.

If there is no character region at step ST303, it is a dot photo original 153.

If there is no photo region at step ST302, it is checked if character region is present in the dot
20 region or not (step ST304). If there is a character region in the dot region, it is a dot background original 154. If there is no character region in the dot region, it is further checked if there is character region outside the dot region (step ST305). If there
25 is no character region outside the dot region, it is a dot photo original 153. If there is a character region outside the dot region, it is a rectangle

discrimination candidate original 152.

If there is no dot region at step ST301, it is checked if photo region is present or not (step ST306). If there is no photo region, it is a uniform background original 156. If there is a photo region, it is further checked if character region is present or not (step ST307). If there is no character region, it is a continuous gradation photo original 155. If there is a character region, it is a rectangle discrimination candidate original 152.

By this process, the input image data is determined in any one of rectangle discrimination candidate original 152, dot photo original 153, dot background original 154, continuous gradation photo original 155, and uniform background original 156.

FIG. 4 is a flowchart showing the detail of image type determining process as an example in the image determining unit 103 of the image processing apparatus of the present invention, which is a flowchart of process corresponding to the rectangle discrimination candidate original 152 shown in FIG. 3.

When determined to be a rectangle discrimination candidate original 152, the complicatedness of the layout structure is verified, and it is classified into rectangle discriminative original or indiscriminative original, and at this time, as an index of measuring the complicatedness of the layout structure, the degree

of overlapping of rectangular regions may be measured. The degree of overlapping of rectangles may be directly verified, but when the number of rectangular regions is increased, it is estimated that the number of times of comparison increases dramatically. Accordingly, by voting the rectangle size in the two-dimensional voting space being prepared, the degree of overlapping may be estimated from the state of the voting space (step ST401).

10 This voting space is for measuring the degree of overlapping of rectangular regions, and its resolution may be lower than the resolution of the original image. Voting is done by adding the feature such as rectangle size of the region to the position where the coordinate position of the rectangular region is converted into
15 the coordinate position of the voting space. An example of rectangle size is width, height or area of the rectangle. Besides, the voting value may be weighted according to the attribute of the rectangular
20 region, that is, the character, photograph, drawing, table, dot or other attribute. For example, the attribute having a great effect on the layout structure, such as photograph, drawing and table is provided with a large weight, and the character has a small weight,
25 so that the voting value is large in the overlapped region of photograph or drawing and table. Considering the complicatedness of the layout structure,

overlapping of photograph or drawing and table is classified into a complicate category. Therefore, in this case, it is easy to regard as a complicated structure. For faster processing, moreover, it is also possible to limit the rectangular region to be voted. For example, a small character region does not always have a large effect in determination of layout structure. In such a case, by limiting the rectangle size to be voted, the number of times of voting is saved, and a faster processing is expected. However, if the character region existing in image data is composed of small character regions alone, it cannot be always ignored. In such a case, it is possible to adjust the limitation depending on the state of the pixel attribute data which is the output of the region discriminating unit 102.

When voting of rectangle size in all voting spaces is over, the feature quantities in the voting spaces are measured (step ST402). As the feature quantity, for example, the statistic value of maximum or variance may be used, or, regarding the voting space to be a multi-value image, the region may be extracted after binary processing. In the former case, it is possible to determine by comparison between the calculated value and the preset threshold, and in the latter case it is possible to determine by measuring the graphic feature of the extracted region. At step ST402, the former

example is employed. In this case, if the maximum (max) or variance (var) is smaller than the threshold (a) or (b), the layout structure is regarded not complicated, and is determined to be a rectangle discriminative original 157, and if larger, to the contrary, the layout structure is regarded complicated, and is determined to be an indiscriminative original 158 (step ST403).

This is the detailed description of the image type determining unit 103, and, as a result, the input image data is determined as any one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background original 156, rectangle discriminative original 157, and indiscriminative original 158.

FIG. 5 is a flowchart showing the detail of data conversion process as an example in the data converting unit 104 of the image processing apparatus, which is a flowchart of the process corresponding to step ST205 in FIG. 2. The data conversion process is a process for changing the format of the input image data by making use of the determining result of image type.

The image type information 161 is the output of the image type determining unit 103, and expresses the type of input image data, which is one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background

original 156, rectangle discriminative original 157,
and indiscriminative original 158.

First, it is checked if the image type information
161 is an indiscriminative original or not (step ST501).

5 If not indiscriminative original, next it is checked if
rectangle discriminative original or not (step ST502).

In the case of rectangle discriminative original,
making use of the information of the pixel attribute
obtained in the region discriminating unit 102, the
10 data conversion process is executed on the input image
data in every rectangular region (step ST503).

Data conversion process is, for example, change of
resolution, compression rate, or number of colors. A
rule of data conversion process may be preset in every
15 pixel attribute, and the data conversion process may be
done according to this rule. For example, in the case
of dot photo region or continuous photo region, if the
resolution is lowered or the compression rate is raised,
image deterioration may not be obvious, and the
20 quantity of information can be curtailed. Or if only
black characters are present in the character region,
the multi-value data may be converted into two-value
data, so that the quantity of information can be
curtailed. In this way, by presetting a specific rule
25 of data conversion process in every pixel attribute, it
is possible to convert into efficient image data.

As a result of data conversion process, converted

image data 162 is output.

If it is not rectangle discriminative original at step ST502, the entire image is uniformly processed by data conversion (step ST504). As uniform data
5 conversion process, for example, in the case the image type information 161 is dot photo original or continuous gradation photo, if the resolution is lowered or the compression rate is raised, image deterioration may not be obvious, so that the quantity
10 of information may be curtailed. Or when the image type information 161 is uniform background original and there are only black characters, the multi-value data may be converted into two-value data, so that the quantity of information can be similarly curtailed. In
15 this way, similarly to at step ST503, by presetting a specific rule of data conversion process in every image type, it is possible to convert into efficient image data. In this case, unlike step ST503, without processing data conversion in every rectangular region,
20 since the same process is applied on the entire image, the processing speed is higher.

As a result of data conversion process, similarly to at step ST503, converted image data 162 is output.

In the case of indiscriminative original at step
25 ST501, without processing data conversion by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is

directly output as corrected image data (step ST505).
Meanwhile, the data conversion process (step ST503 and
step ST504) is not limited to processing of input image
data such as change of resolution, compression rate and
5 number of color, but also includes, as mentioned above,
the process of converting the attribute region
information into image data.

Thus, since the data conversion is processed
according to the determined type of the image data by
10 determining the type of the input image data from the
result of discriminating the region, it is possible
to convert into efficient image data having less
deterioration of image quality.

<Second Embodiment>

15 A second embodiment of the present invention is
described next. The second embodiment is shown in
FIG. 6, and relates to an image processing apparatus
for correcting image data by appropriate density
conversion or filter processing, according to the
20 result of discriminating the type of image.

FIG. 6 schematically shows the constitution of the
image processing apparatus of the second embodiment.
In FIG. 6, the image processing apparatus comprises an
image input unit 101, a region discriminating unit 102,
25 an image type determining unit 103, an image correcting
unit 106, and an image forming unit 105, in which the
image correcting unit 106 corresponds to the data

converting unit 104 in the first embodiment shown
in FIG. 1. The image input unit 102, region
discriminating unit 102, image type determining unit
103, and image forming unit 105 are already explained,
5 and the image correcting unit 106 is described below.

FIG. 7 is a flowchart showing an example of
document processing procedure in the image processing
apparatus shown in FIG. 6. Of the flowchart of the
constitution in FIG. 1 shown in FIG. 2, herein, the
10 data conversion process (step ST205) is changed to
image correction process (step ST207).

After determining the document type of the image
data input in the image type determining unit 103, in
the image correcting unit 106, the image data is
15 corrected by appropriate density conversion or filter
processing according to the document type corresponding
to the type of the image data (step ST207).

FIG. 8 is a flowchart showing the detail of image
correction process as an example in the image
20 correcting unit 106, which is a flowchart of the
process corresponding to step ST207 shown in FIG. 7.

The image type information 161 is the output of
the image type determining unit 103, and expresses the
type of input image data, which is one of dot photo
25 original 153, dot background original 154, continuous
gradation photo original 155, uniform background
original 156, rectangle discriminative original 157,

and indiscriminative original 158.

First, it is checked if the image type information 161 is an indiscriminative original or not (step ST601). If not indiscriminative original, next it is checked if
5 rectangle discriminative original or not (step ST602). In the case of rectangle discriminative original, making use of the information of the pixel attribute obtained in the region discriminating unit 102, the image correction process is executed on the input image
10 data in every rectangular region (step ST603).

Image correction process is, for example, density conversion process or filtering process. A rule of image correction process may be preset in every pixel attribute, and the image correction process may be done
15 according to this rule. For example, in the case of character region, high pass filter may be processed so that the characters may be more clear, or in the case of dot photo region, low pass filter may be processed to obtain a smooth image without moiré. As a result,
20 being corrected into image data of high quality, it may be output as corrected image data 163. In this way, by presetting a specific rule of image correction process in every pixel attribute, it is possible to correct into image data of high quality.

25 If it is not rectangle discriminative original at step ST602, the entire image is uniformly processed by image correction (step ST604). As uniform image

correction process, for example, in the case of uniform background original, the entire image may be processed by high pass filter so that the characters may be clear, or in the case of dot photo region, the entire image may be processed by low pass filter to obtain a smooth image without moiré. In this way, similarly to at step ST603, by presetting a specific rule of image correction process in every image type, it is possible to correct into image data of high quality. In this case, unlike step ST603, without processing image correction in every rectangular region, since the same process is applied on the entire image, the processing speed is higher. As a result of image correction process, similarly to at step ST603, corrected image data 163 is output.

In the case of indiscriminative original at step ST601, without processing image correction by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is directly output as corrected image data (step ST605).

Thus, since the image correction is processed according to the determined type of the image data by determining the type of the input image data from the result of discriminating the region, it is possible to obtain image data of high quality.

<Third Embodiment>

A third embodiment of the present invention is

described below. The third embodiment is shown in FIG. 9, and relates to an image processing apparatus for selecting the image format to be stored, converting into this format, and storing, according to the result of discriminating the type of image when filing the image.

FIG. 9 schematically shows the constitution of the image processing apparatus of the third embodiment. In FIG. 9, the image processing apparatus comprises an image input unit 101, a region discriminating unit 102, an image type determining unit 103, an image format changing unit 107, and an image forming unit 105, in which the image format changing unit 107 corresponds to the data converting unit 104 and an image memory unit 108 corresponds to the image forming unit 105 in the first embodiment shown in FIG. 1. The image input unit 102, region discriminating unit 101, and image type determining unit 103 are already explained and are omitted herein. An image memory unit 108 is the output destination after conversion of image format, and is substantially regarded to operate same as the image forming unit 105. Therefore, the image format changing unit 107 is described below.

FIG. 10 is a flowchart showing an example of document processing procedure in the image processing apparatus shown in FIG. 9. Of the flowchart of the constitution in FIG. 1 shown in FIG. 2, herein, the

data conversion process (step ST205) is changed to image format changing process (step ST208).

After determining the document type of the image data input in the image type determining unit 103, in the image format changing unit 107, the image format suited to be stored in the image memory unit 108 is selected according to the document type corresponding to the type of the image data, and it is converted to this format (step ST208).

FIG. 11 is a flowchart showing the detail of image format conversion process as an example in the image format changing unit 107, which is a flowchart of the process corresponding to step ST208 shown in FIG. 10.

The image type information 161 is the output of the image type determining unit 103, and expresses the type of input image data, which is one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background original 156, rectangle discriminative original 157, and indiscriminative original 158.

First, it is checked if the image type information 161 is an indiscriminative original or not (step ST701). If not indiscriminative original, next it is checked if rectangle discriminative original or not (step ST702). In the case of rectangle discriminative original, making use of the information of the pixel attribute obtained in the region discriminating unit 102, the

image format conversion process is executed on the input image data in every rectangular region (step ST703).

The image format includes, for example, JPEG
5 format and TIFF (G4) format. A rule of image format conversion process may be preset in every pixel attribute, and the image format conversion process may be done according to this rule. For example, in the case of character region, the quantity of data can be
10 curtailed by converting into the TIFF (G4) format, and it is changed into efficient image data. Or, in the case of dot photo region or continuous gradation photo region, by converting into the JPEG format, the quantity of data can be compressed while suppressing
15 deterioration of image quality, and in this case, too, it is changed into efficient image data. As a result, it can be stored as format converted image data 164. In this case, from one image data, plural formats of image data are generated. When storing, therefore,
20 they may be stored individually. At this time, the structure of the original image data and the format converted image data name generated therefrom may be saved as reference file, and when restoring, by referring to this reference file, the original image
25 data may be reconstructed from the format converted image data 164. In this way, by presetting a specific rule of image format conversion process in every pixel

attribute, it is possible to convert into image data format of high efficiency by curtailing the quantity of data.

If it is not rectangle discriminative original at
5 step ST702, the entire image is uniformly processed by
image format conversion (step ST704). As uniform image
format conversion process, for example, in the case of
uniform background original, which does not include
photograph, by converting into TIFF (G4) format, the
10 quantity of data can be curtailed, or in the case of
dot photo original or continuous gradation photo
original, by converting into the JPEG format, the
quantity of data can be compressed while suppressing
deterioration of image quality. In this way, similarly
15 to at step ST703, by presetting a specific rule of
image format conversion process in every image type, it
is possible to convert into image data format of high
efficiency reduced in the quantity of data. In this
case, unlike step ST703, without processing image
20 format conversion in every rectangular region, since
the same process is applied on the entire image, the
processing speed of image format conversion is higher,
and plural image formats are not generated, and
therefore the reference file is not needed, and the
25 original image data can be restored at high speed from
the stored format converted image data. As a result
of image format conversion process, similarly to at

step ST703, it can be stored as format converted image data 164.

5 In the case of indiscriminative original at step ST701, without processing image format conversion by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is directly output as format converted image data (step ST705).

10 Thus, since the image format conversion is processed according to the determined type of the image data by determining the type of the input image data from the result of discriminating the region, it is possible to change into image data of high efficiency, and the quantity of information when storing can be
15 curtailed.

<Fourth Embodiment>

A fourth embodiment of the present invention is described below. The fourth embodiment is shown in FIG. 12, and relates to an image processing apparatus
20 for selecting the application to be started, determining the starting parameter, and starting the application, according to the result of determining the type of the image.

FIG. 12 schematically shows the constitution of
25 the image processing apparatus of the fourth embodiment. In FIG. 12, the image processing apparatus comprises an image input unit 101, a region discriminating unit 102,

an image type determining unit 103, an application starting unit 109, and an application processing result forming unit 110, in which the application starting unit 109 corresponds to the data converting unit 104 and the application processing result forming unit 110 corresponds to the image forming unit 105 in the first embodiment shown in FIG. 1. The image input unit 101, region discriminating unit 102, and image type determining unit 103 are already explained and are omitted herein. The application processing result forming unit 110 is the output destination of the result of processing after starting the application, and is substantially regarded to operate same as the image forming unit 105. Therefore, the application starting unit 109 is described below.

FIG. 13 is a flowchart showing an example of document processing procedure in the image processing apparatus shown in FIG. 12. Of the flowchart of the constitution in FIG. 1 shown in FIG. 2, herein, the data conversion process (step ST205) is changed to application starting process (step ST209) and the image forming process (step ST206) is changed to application processing result forming process (step ST210).

After determining the document type of the image data input in the image type determining unit 103, in the application starting unit 109, an application suited to image processing according to the type of the

document corresponding to the type of the image date is selected, the starting parameter is determined, and the application is started (step ST209).

FIG. 14 is a flowchart showing the detail of application starting process as an example in the application starting unit 109, which is a flowchart of the process corresponding to step ST209 shown in FIG. 13.

The image type information 161 is the output of the image type determining unit 103, and expresses the type of input image data, which is one of dot photo original 153, dot background original 154, continuous gradation photo original 155, uniform background original 156, rectangle discriminative original 157, and indiscriminative original 158.

First, it is checked if the image type information 161 is an indiscriminative original or not (step ST801). If not indiscriminative original, next it is checked if rectangle discriminative original or not (step ST802). In the case of rectangle discriminative original, making use of the information of the pixel attribute obtained in the region discriminating unit 102, the application is started on the input image data in every rectangular region, and various image processings are done (step ST803).

The application includes, for example, image filing, printing, facsimile transmission, layout

understanding, character recognition, rule extraction and other image processings. A rule of application for starting may be preset in every pixel attribute, and the application starting process may be done according to this rule. For example, in the case of character region, by layout understanding, the column setting or other document structure may be recognized, and the characters may be encoded by character recognition. Or, in the case of dot photo region or continuous gradation photo region, the image filing may be started in order to save the image, or when printing, if the region is color, by attaching a starting parameter of color, the printer at the output destination may be automatically changed to a color printer. The result processed by the application is the application processing result data 165, which may be provided in various formats such as printout, file, or character recognition result. By thus presetting the rule of application starting process in every pixel attribute, as soon as the image data is input, various processings may be done automatically.

If it is not rectangle discriminative original at step ST802, the entire image is uniformly processed by starting the application (step ST804). As uniform image format conversion process, for example, in the case of uniform background original, which does not include photograph, by layout understanding, the

document structure such as paragraph is recognized, and the character can be encoded by character recognition, or in the case of dot photo original or continuous gradation photo original, the image filing may be started for saving the image, or printing or facsimile transmission can be done directly. The result of processing by the application is, similarly to at step ST803, it is the application process result data 165, and various formats may be provided, such as printout, file and character recognition result.

In the case of indiscriminative original at step ST801, without application starting process by using the information of the pixel attribute obtained in the region discriminating unit 102, the input image data is directly output as application process result data, or by starting the image filing or the like, the image data is directly stored as file, and the processing may be selected later by the determination of the user (step ST805).

Thus, since the application for processing the image is started according to the determined type of the image data by determining the type of the input image data from the result of discriminating the region, it is possible to perform various processes as soon as the image data is input, so that the labor may be saved.

As described herein, the image processing apparatus of the present invention is designed to

incorporate a document image through an image input unit 101, extract one physically or logically coupled from the status of data of each pixel and adjacent pixels in the region discriminating unit 102 as one
5 region, measure the feature quantities such as position, size, shape, structure and density distribution of each region on the image, and discriminate the measured result as a region having the attribute such as character, photograph, dot or the like as the document
10 constituent element according to a predetermined rule. On the basis of the attribute information or the like, the type of the document depending on the type of the image data is determined from the feature such as complicatedness of the entire document image input in
15 the image type determining unit 103, and the image data format is converted in the data converting unit 104 depending on the type of the document corresponding to the type of the image data.

In the image correcting unit 106, by processing to
20 correct the image data by adequate density conversion or filter processing according to the type of the document corresponding to the type of the image data, in the image format changing unit 107, the image format suited to be stored in the image memory 108 is selected
25 according to the document type corresponding to the type of the image data, and it is processed to be converted into this format.

Further, in the application starting unit 109, selecting an application suited to image processing according to the type of the document corresponding to the type of the image data, the starting parameter is
5 determined, and it is made possible to process to start the application.

Therefore, in the original image data input in the apparatus, by extracting the region by distinguishing the different document elements such as character,
10 photograph, drawing, table, and dot, the feature quantities such as presence or absence of key region such as dot and photograph, and complicatedness as document structure from the degree of overlapping of rectangular region are determined, and hence it is
15 possible to determine what kind of document is the input image data, and by making use of the determining result, it is possible to convert into efficient image data less in deterioration of image quality, or correct image in order to obtain image data of high quality.

20 When saving as image file, the format suited to the image data can be selected automatically, and efficient filing is realized.

Further, as soon as the document image data is input, the image processing application is selected and
25 started automatically, so that the labor is saved.

Further, as other embodiments relating to the image processing apparatus, image forming apparatus,

and image processing method of the present invention, fifth to twelfth embodiments are described specifically below while referring to the accompanying drawings.

<Fifth Embodiment>

5 A fifth embodiment is shown in FIG. 15, which presents an image forming apparatus for composing an image quality parameter as shown in FIG. 15, in addition to the first embodiment. An electronic copier usually comprises an image input unit such as scanner, 10 an image processing unit, and an image forming unit such as printer. The electronic copier also includes an operation unit (control panel) to be used by the user for making various settings. The operation unit has an image quality parameter input unit as described 15 later, and an image quality adjusting parameter is input according to the user's preference of image quality.

That is, in FIG. 15, the image forming apparatus comprises an image input unit 1, a page information 20 discriminating unit 2, an image processing unit 3, and an image forming unit 4. The image forming apparatus is connected with an image parameter input unit 31 for inputting an image quality adjusting parameter according to the user's preference of image quality, 25 image quality storing unit 32 for storing the image quality parameter input by the image quality parameter input unit 31, and an image quality parameter deciding

unit 33 for deciding the image quality parameter to be processed in the image processing unit 3 on the basis of the image quality parameter stored in the image quality parameter storing unit 32.

5 Referring to FIG. 15, the embodiment of the present invention is described in detail below.

First, the image input unit 1 is, for example, a color CCD scanner, which reads the original color image, and separates into electric signals of three primaries, R (red), G (green), B (blue), vertically and
10 horizontally, converts into 8-bit digital data of each color in each unit pixel (for example, 400 dpi), and outputs as R, G, B, respectively.

Image signals of R, G, B are input into the page
15 information discriminating unit 2 for discriminating the type of the entire image, and the image processing unit 3.

FIG. 16 shows an example of the image processing unit 3, which is composed of a color converting unit 51,
20 a space filter 52, a black color unit 53, a γ -correction unit 54, and a gradation processing unit 55, and in each block the page information output by the page information discriminating unit 2 is input together with the image signals output by all blocks.

25 In the color converting unit 51, signals of R, G, B input from the scanner are converted in the following formula 1, and signals of C (cyan), M (magenta), and Y

(yellow) corresponding to the signals of the image forming unit 4 are obtained.

$D_r = -\log R$

$D_g = -\log G$

5 $D_b = -\log B$

$$\begin{pmatrix} C \\ M \\ Y \end{pmatrix} = \begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{pmatrix} \begin{pmatrix} D_r \\ D_g \\ D_b \end{pmatrix}$$

This operation is composed of the circuit shown in FIG. 17. The color converting unit 51 is composed of
10 look-up tables (LUT) 61a to 61c for log conversion, nine multipliers 62a to 62i for 3×3 matrix operation, and three adders 63a to 63c.

In the color converting unit 51, the method of use of page discrimination signal is, for example, as
15 follows. First, as the types of original image data mentioned in the first embodiment, or the types of individual documents (called page discrimination information hereinafter), uniform background (having characters), dot background (having characters), dot
20 photo (having photo only), and continuous photo (having photo only) are defined. In these four types of images, generally, it is known that the blue color is strong in the case of continuous photo using photographic printing paper. It is therefore preferred to change
25 the color reproducibility only in the case of continuous photo. To change the color reproducibility, it is necessary to change the coefficients all to a_{33}

of the color conversion matrix. That is, preparing coefficients a_{11} to a_{33} for continuous photo, and coefficients a_{11} to a_{33} for other image, they are changed over on the basis of the page discrimination information.

The space filter 52 is composed of, for example, a high frequency component calculating unit 71, a multiplier 72 for operating the weight of high frequency component, and a subtracting unit 73 of the original image as shown in FIG. 18. The high frequency component calculating unit 71 is to operate, for example, 3×3 Laplacian filter, and emphasize the high frequency component of the original image, and it is composed of a filter as shown in FIG. 19.

FIG. 20 shows a specific example of circuit constitution of the space filter 52, in which the high frequency component calculating unit 71 is composed of flip-flop circuits 71a to 71f, multipliers 71g to 71p, and adder 71q. This circuit is required for each color of C, M and Y. Herein, the weighting coefficient K is an image quality parameter determined by the image quality parameter deciding unit 33, and by adjusting this weighting coefficient K, the sharpness of image can be adjusted.

The method of using the page discrimination information in this space filter 52 is the method of changing the filter coefficient or weighting

coefficient K on the basis of the page discrimination information shown in FIG. 19. For example, in the case of uniform background or continuous photo, the filter weighting coefficient K is large, and in the case of dot background or dot photo, the weighting coefficient K is set smaller in order to suppress dot moiré.

The black color unit 53 processes to generate signal of C (cyan), M (magenta), Y (yellow), and K (black) from the signals of C (cyan), M (magenta), and Y (yellow), and, for example, the UCR processing is done as shown in the formula below.

$$K = a \times \min(C, M, Y)$$

$$C' = C - K$$

$$M' = M - K$$

$$Y' = Y - K$$

a: parameter for determining the amount of black color

This operation is composed of, for example, the circuit shown in FIG. 21. This circuit is composed of comparators 81a, 81b, selectors 82a, 82b, and subtractors 83a to 83c.

The method of utilizing page discrimination in the black color unit 53 is, for example, a method of changing the black color rate (a) in every type of image. In the uniform background or dot background having characters, by setting the black color rate (a) higher, black characters are reproduced more easily in

a single black color, and the character reproducibility is enhanced. In the case of dot photo or continuous photo, the color reproducibility is improved by setting the black color rate (a) lower.

5 The γ -correction unit 54 is a block used for correcting the density characteristic of the printer unit of each color of C, M, Y, and adjusting the density by the user, and a simplest constitution is a look-up table (LUT) 90 of input of 8 bits and output of
10 8 bits as shown in FIG. 22. In this table, for example, a density conversion curve as shown in FIG. 23 is set. The default is, for example, a curve of 0 (a curve equal in input and output), and when the user adjusts the density, a density curve corresponding to -3 to +3
15 is selected and set according to the determined image quality parameter.

 In the γ -correction unit 54, the following setting method using page discrimination information is available. For example, in the case of uniform
20 background or dot background having characters, as the γ -curve used as γ -correction, a high- γ table is prepared and set. As a result, the reproducibility of characters is enhanced. On the other hand, in the case of dot photo or continuous photo, a table of linear
25 input and output is set for improving the gradation reproducibility.

 The gradation processing unit 55 is to process to

convert 8-bit signal of C, M, Y, K into, for example, 1 bit (binary), and the error diffusion method is known as a representative method.

In the error diffusion method, a binary error of
5 an already binary peripheral pixel is multiplied by a certain weighting coefficient, and this product is added to the density of the pixel of notice, and a binary value is obtained by fixed threshold. FIG. 24
10 is a structural block diagram of binary process by error diffusion method. In FIG. 24, the binary circuit includes an input image signal 40, a correcting unit 41 for correcting image information of pixel of notice, a corrected image signal 411, a binary unit 42 for obtaining a binary value from the corrected image
15 information of pixel of notice, a binary image signal 421, a binary error calculating unit 43 for calculating the binary error of binary pixel of notice, a binary error signal 431, a weighting coefficient memory unit 44 for storing the weighting coefficient for
20 calculating the weighting error, a weighting error calculating unit 45 for calculating a weighting error by multiplying the binary error calculated in the binary error calculating unit 43 by the weighting coefficient of the weighting error memory unit 44, a
25 weighting error signal 451, an error memory unit 46 for storing the weighting error calculated in the weighting error calculating unit 45, and an image correction

signal 461. The binary process of the error diffusion method is described in detail below.

The input image signal 40 of the γ -correction unit 55 is corrected by the image correction signal 461 described later, and a corrected image signal 411 is output. The corrected image signal 411 is compared with a binary threshold Th (for example, in 80h, "h" denotes hexadecimal notation) in the binary unit 42, and when the corrected image signal 411 is larger than the binary threshold Th , "1" (black pixel) is output as binary image signal 421, and "0" (white pixel) is output when smaller. In the binary error calculating unit 43, the difference between the corrected image signal 411 and binary image signal 421 (herein, however, it is 0h when binary image signal is "0", and ffh when "1") is calculated, and it is output as binary error signal 431. In the weighting error calculating unit 45, the binary error signal 431 is multiplied by the weighting coefficients A, B, C, D ($A=7/16$, $B=1/16$, $C=5/16$, $D=3/16$) of the weighting coefficient memory unit 44, and the weighting error 451 is calculated. Herein, the * mark in the weighting coefficient memory unit 44 indicates the position of pixel of notice, and the binary error of the pixel of notice is multiplied by the weighting coefficients A, B, C, D, and the weighting error of four peripheral pixels of the pixel of notice (pixels corresponding to the positions of the

weighting coefficients A, B, C, D) is calculated. The error memory unit 46 is to store the weighting error 451 calculated in the weighting error calculating unit 45, and the weighting errors of four pixels calculated in the weighting error calculating unit are added and stored in the regions of eA, eB, eC, eD corresponding to the pixel of notice *. The image correction signal 461 is a signal at position of *, and is a cumulative signal of weighting errors of four pixels calculated in the above procedure.

In the above explanation of gradation processing unit 55, the output is binary, but by preparing a plurality of binary thresholds Th and comparing with the input image signal, multi-value processing is same as in binary value.

In the gradation processing unit 55, for example, the page discrimination information is utilized as described below. First, FIGS. 25A and 25B show two cases of output of the gradation processing unit 55.

In FIG. 25A, the laser modulator, not shown, of the image forming unit 4 is modulated in the unit of two pixels, and as determined from the diagram, the resolution is $1/2$, but since the pixel size is small even at the same gradation level, the gradation output withstands fluctuation of recording, and an image can be formed on the basis of a stable output.

In FIG. 25B, on the other hand, the laser is

driven in the unit of one pixel, and the resolution is high although stability of density fluctuation is insufficient. That is, the one-pixel modulation method of high resolution is employed in the case of uniform background or dot background having characters, and the two-pixel modulation method of high density stability is employed in the case of dot photo or continuous photo.

Examples of use of page discrimination information in each process are presented herein, but the method of use is not limited to these examples alone, but various methods may be considered.

So far is shown an example of structure of the image processing unit 3, and thus processed signals of C (cyan), M (magenta), Y (yellow), and K (black) are input in the image forming unit 4, and an image is formed and output on a paper.

In such constitution, an embodiment of the page information discriminating unit 2 in the fifth embodiment operating same as in the first embodiment is described below.

FIG. 26 shows an example of structure of the page information discriminating unit 2. The page information discriminating unit 2 is composed of region discriminating unit 102 and original type determining unit 103 shown in FIG. 1.

The page information discriminating means 2 takes

in a document image, in the region discriminating means
21, one coupled physically or logically from the
situation of each pixel and vicinal pixel data is
extracted as one region, feature quantities of each
5 region such as position on the image, size, shape,
structure, and density distribution are measured, and
the result of measurement is discriminated as the
region having attribute such as character, photograph,
and dot as the document constituent elements according
10 to a preset rule. On the basis of the attribute
information and others, in the original type
determining unit 103, the type of the document is
decided from the features of the entire input document
image, and the image data format can be converted
15 according to the type of the document.

The structure and operation of the region
discriminating unit 102 and original type determining
unit 103 are same as in the first embodiment shown in
FIG. 1 and after, and their description is omitted
20 herein.

<Sixth Embodiment>

The foregoing description relates to an example of
using the page discrimination information only when
determining the processing conditions in each process
25 of the image processing unit, but in a sixth embodiment
shown in FIG. 27, rectangle discrimination information
(image type of plural regions) is used together with

the page discrimination information.

In FIG. 27, the page discrimination information and rectangle discrimination information are used as the processing conditions in each process of the image processing unit. As compared with the constitution in FIG. 15, a region discriminating unit 6 is added, and together with the page discrimination information output by the page information discriminating unit 2, the rectangle discrimination information output by the region discriminating unit 6 is input into the image processing unit 7. By using both page discrimination information and rectangle discrimination information, more specific parameter setting is possible in the image processing unit 7.

For example, the page discrimination information is the information shown in FIG. 28A. Herein, "0. Region discrimination" shows that the rectangle discrimination information output by type region discriminating unit 6 is valid, and "1. Uniform background to 4. Continuous photo" means that the page discrimination information output by the page information discriminating unit 2 is valid.

When the page discrimination information is "0. Region discrimination," using the discrimination result of the rectangle unit of the region discriminating unit 3, the image processing condition is changed in the rectangle unit in the image processing unit 3. On the

other hand, when the page discrimination information is "1. Uniform background to 4. Continuous photo," this information is used as the discrimination information in the page unit, and the image processing unit 4 sets the image processing condition on the basis of this information, and executes a specific processing in the image unit. Thus, by using the page discrimination information, as compared with the conventional image copying apparatus generally having five operation modes shown in FIG. 28B as the operation modes (operation modes corresponding to the type of the original to be copied), an automatic mode can be provided as shown in FIG. 28C (the mode for selecting a mode for executing specific process image unit and a mode for executing the process by changing the processing condition in the unit of rectangle or pixel, automatically on the basis of the page discrimination information and outputting), so that an image of a higher image quality than in character/photo mode can be obtained.

When the page discrimination information is "5. Indiscriminative," it means all of "0. Region discrimination to 4. Continuous photo" are invalid, and none of the discrimination information can be used. Therefore, in the image processing unit 7, specific processing is done in the entire image without using discrimination information, or the type of image discriminated in the pixel unit in a method explained

below, and the image is processed.

<Seventh Embodiment>

A seventh embodiment is shown in FIG. 29, in which the discrimination process in pixel unit is further
5 added to the first embodiment. FIG. 29 shows an example of structure of an image processing unit 7 when executing image processing by discriminating in the pixel unit.

The image processing unit 7 shown in FIG. 29 is
10 similar to the image processing unit 3 for inputting page discrimination information shown in FIG. 16, except that a pixel unit discriminating unit 56 is added. In the constitution in FIG. 16, specific page discrimination information for entire image is input in
15 the color converting unit 51 to gradation processing unit 55, and each image processing is determined in the image processing condition on the basis of its page discrimination information. In the constitution of the image processing unit 7 in FIG. 29, instead of the page
20 discrimination information, the pixel unit discriminating unit 56 discriminates the type of image in the pixel unit on the basis of the input image information, and processes by setting the image processing condition in each image processing block on
25 the basis of this discrimination information.

The processing method in the pixel unit discriminating unit 56 includes, for example, a method

of separating three regions of character, photo, and dot photo, as disclosed in "Block Separate Transformation Method (BSET)" in "Discrimination Processing Method of Dot Photograph" (J. of Japan Society of Electronics, Information Communication, Vol. J70-B, No. 2, February 1987).

In this method, the object image is divided into blocks, and three regions are separated by density change within blocks. At this time, it is intended to make use of nature of density changes, that is:

- Photograph is small in density change in block.
- Character and dot photograph are large in density change in block.
- Character is large in period of density change.
- Dot photograph is small in period of density change.

The detail is described below.

- (1) The object image is divided into blocks of $(m \times n)$ pixels.
 - (2) Maximum density signal D_{\max} and minimum density signal D_{\min} in block are determined, and maximum density difference signal ΔD_{\max} in block is calculated.
 - (3) Comparing preset threshold $Th1$ and ΔD_{\max} , photo region and non-photo region (character and dot photo region) are separated in the following condition.
- $$\Delta D_{\max} \leq Th1 \quad \text{Photo region}$$

$\Delta d_{max} > Th1$ Non-photo region

(4) Each pixel in block is coded into binary signal (0/1) by average signal D_a of signal in block.

(5) The number of times of 0/1 change K_h between
5 pixels consecutive in the main running direction in block is determined. Similarly, in the sub-scanning direction, the number of times of changes K_v is determined.

(6) Comparing preset threshold $Th2$ and K_h and K_v ,
10 the character region and dot photo region are separated in the following condition.

$K_h \geq Th2$ and $K_v \geq Th2$ Dot photo region

$K_h < Th2$ and $K_v < Th2$ Character region

In this procedure, the character, photo, and dot
15 photo regions can be separated.

FIG. 30 shows an example of circuit configuration of pixel unit discriminating unit 56, which is a circuit for calculating the maximum density difference Δd_{max} in 4×4 window (shaded areas showing pixel of
20 notice) shown in FIG. 31. This circuit is composed of selector 12a, comparators 12b to 12g, and subtractor 12h.

<Eighth Embodiment>

An eighth embodiment is shown in FIG. 32, in
25 which a case of setting the processing condition of pixel unit discriminating unit 56 by using page discrimination information is explained, and this is an

effective method for enhancing the precision of discrimination.

FIG. 32 shows a constitution of using page discrimination information in the pixel unit discriminating unit 8. The operation of the page information discriminating unit 2 is as explained already, and the pixel unit discriminating unit 8 receives the page discrimination information together with the input image data of the image input unit 1, and sets a parameter for discrimination on the basis of the page discrimination information.

First, as page discrimination information, four pieces of information shown in FIG. 28D are output, and a discriminating method of pixel unit is explained in a case of discriminating the character region by using the maximum density difference ΔD_{max} . When using the maximum density difference ΔD_{max} , it is known that separation into dot region and character region is difficult. Therefore, using page discrimination information, it is set at threshold $Th=th1$ in the uniform background region, at $Th=th2$ in the dot photo region, and $Th=th3$ in the dot photo and continuous photo region (where $th1>th2>th3 \approx 0$). By thus setting, the photo region is not falsely discriminated as character region, and characters in the dot background region which are difficult to discriminate can be lowered in the rate of false discrimination in the

non-character region, so that very effective pixel unit discrimination may be realized.

<Ninth Embodiment>

5 A ninth embodiment is shown in FIGS. 28A and 29,
in which the duration of time necessary for
discriminating process is evaluated by using "Time
over" prepared as page discrimination information, and
it is decided whether or not to use the page
discrimination information according to the result.
10 Thus, the certainty of region recognition can be
attained as far as possible in the range of processing
time.

That is, in FIG. 28A, "6. Time over" is provided
as page discrimination information. The original type
15 discriminating unit 22 shown in FIG. 26 is more
preferably realized by the software, and therefore the
processing time differs depending on the type of the
original to be input. Therefore, the discriminating
process may not be terminated within the required
20 processing time of the image forming apparatus. This
page discrimination information "6. Time over" is, by
measuring the time required for discriminating process,
set when it is not terminated within the processing
time specified in this system. In such a case, the
25 image processing unit 7 discriminates in the pixel unit
without using page discrimination information as
explained already in, for example, FIG. 29, and

processes the images according to this discrimination information, thereby finishing within the preset range of processing time.

<Tenth Embodiment>

5 A tenth embodiment is shown in FIG. 33, and using "Indiscriminative" prepared as page information similarly, it is designed to evaluate the discrimination precision of discriminating process, and execute discriminating process appropriately according to it.

10 That is, the original type discriminating unit 22 outputs information such as "5. Indiscriminative" as shown in FIG. 28A. It corresponds to the flow of discriminating process at step ST403 in FIG. 4.

FIG. 33 shows a constitution of this embodiment.

15 The image forming apparatus in FIG. 33 comprises an image input unit 1, a page information discriminating unit 2, an image dividing unit 10, a region discriminating unit 11, a discrimination precision determining unit 12, a selecting unit 13, an
20 image processing unit 14, and an image forming unit 4.

 In this constitution, when the discrimination precision is poor, it is determined to be indiscriminative, and in such a case, therefore, the
 image processing unit 14 or 19 discriminates the pixel
25 unit without using page discrimination information as explained already, for example, in FIG. 29, and it is possible to process images on the basis of this

discrimination information. In this way, effects of poor discrimination result of discrimination precision can be avoided, and processing result of a specific level may be maintained.

5 <Eleventh Embodiment>

 An eleventh embodiment is shown in FIG. 34, and using "Indiscriminative" prepared as page information similarly, it is designed to evaluate the complicatedness of discriminating process, and execute
10 discriminating process appropriately according to it.

 FIG. 34 shows a constitution of this embodiment.

 The image forming apparatus in FIG. 34 comprises an image input unit 1, a page information discriminating unit 2, a complicatedness determining unit 15,
15 an image dividing unit 16, a region discriminating unit 17, a selecting unit 18, an image processing unit 19, and an image forming unit 4.

 In this constitution, when the complicatedness of the object image is very high, it is determined to be
20 indiscriminative, and in such a case, therefore, the image processing unit 14 or 19 discriminates the pixel unit without using page discrimination information as explained already, for example, in FIG. 29, and it is possible to process images on the basis of this
25 discrimination information. In this way, adverse effects of discrimination result when the complicatedness is high can be avoided, and processing

result of a specific level may be maintained.

The foregoing embodiments are representative methods using the page discrimination information, and a further different embodiment is shown in FIG. 35.

5 <Twelfth Embodiment>

A twelfth embodiment is shown in FIG. 35, in which the image is processed preliminarily by plural types of image processing conditions depending on the image information, if obtained without waiting for output of the discrimination result of page information in order to increase the processing speed, it is stored in the memory region, and when the discrimination result is obtained, the result of image processing corresponding to it is read out from the memory region. Thus, by parallel operation of discriminating process of image type and image processing of plural types, the processing speed can be increased on the whole.

10

15

The image forming apparatus in FIG. 35 comprises an image input unit 1, a page information discriminating unit 2, image processing units 25, 26, a storing/reading unit 27, a memory unit 28, and an image forming unit 4. This constitution has two image processing units 25, 26, and memory unit 28 for saving the processing results output by the image processing units 25, 26, and it is designed to output the image by selecting and reading from the stored plural image processing results by the page information

20

25

discriminating unit 2.

In the image processing unit 25 and image processing unit 26, it is designed to process by two kinds of image processing conditions regardless of the page discrimination information, for example, the image processing parameter suited to character image and image processing parameter suited to photo image. The two kinds of image processing results are stored in the memory unit 28, for example, memory or HDD, and when the processing result output by the page information memory unit 2 is uniform background or dot background, the image processing result for character processed by the image processing unit 25 is read out from the storing/reading unit 27, and on the other hand, when the page information output by the page information discriminating unit 2 is dot photo or continuous photo, the image processing result for photo processed by the image processing unit 26 is read out from the memory unit 28 and output.

In such constitution, it is possible to operate processing of the page information discriminating unit 2 and processing of the image processing units 25, 26 parallel (that is, image processing is done in the image processing units 25, 26 without waiting for output of the page information discriminating unit 2), so that high speed operation is possible in the image forming apparatus.

As explained already, the image processing unit 3 shown in FIG. 15 makes use of the page discrimination information used in each image processing shown in FIG. 16, and the relation between the original mode showing the operation mode of the apparatus and the processing condition of page discrimination information and each image processing block is shown in FIG. 36.

In FIG. 36, the page discrimination result shows the page discrimination information shown in FIG. 28A, such as character/photo, character, map, printed photo, and photo in photographic printing paper shows the processing condition of each image processing such as color conversion, background processing, ..., gradation processing, and it means the same condition as when each is selected as the original mode. The processing condition of each image processing for the same page discrimination information is not always the same, and symbols such as A, B, ... denote variations of parameters slightly different from the case when selected as original mode, and it is necessary to divide into proper groups or into further small divisions depending on the image processing.

As explained herein, according to the embodiments of the present invention, if character and photograph are mixed, the character/photo mode is selected as the original mode, and the region or entire image is automatically discriminated as one category, and the

image processing is done so as to obtain the optimum image quality.

Further, in discrimination done by the apparatus in the character/photo mode, not only the discrimination of the region but also discrimination information of entire image are output, and therefore the recognition precision can be enhanced, so that deterioration of image quality due to wrong recognition of type of image can be suppressed.

Further, to decrease the problems of such wrong recognition, such process as to decrease the difference in processing between categories to be discriminated (for example, character and photo) and make the deterioration of image quality due to wrong recognition less obvious even when discriminated falsely, and an output of higher image quality can be obtained as compared with the prior art.

As described specifically herein, the present invention presents an image processing apparatus capable of suppressing deterioration of image quality due to wrong discrimination in region discrimination, and an image forming apparatus and an image processing method capable of forming an image at high quality by processing appropriately depending on the type of the image data.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore,

the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

5

WHAT IS CLAIMED IS:

1. An image processing apparatus comprising:

input means for inputting image data of an original image;

5 discriminating means for extracting a predetermined region by using a feature of pixel of the image data input from the input means, and for discriminating an attribute of the region;

determining means for determining the type of the
10 image data on the basis of the distribution of the regions attribute of which discriminated by the discriminating means; and

processing means for processing the image data as specified depending on the type of the image data
15 determined by the determining means.

2. An image processing apparatus according to claim 1, wherein the determining means includes:

means for determining the type of the image data as at least one type selected from the group consisting
20 of image data of uniform background, image data of dot background in the entire screen, image data of dot photo only, image data of continuous gradation photo only, image data of which region can be discriminated by rectangle, and image data of which region cannot be
25 discriminated by rectangle.

3. An image processing apparatus according to claim 1, wherein the processing means includes:

means for converting at least one of resolution, compression rate, and number of colors of the image data, depending on the type determined by the determining means.

- 5 4. An image processing apparatus according to claim 1, wherein the processing means includes:

 correcting means for correcting the image data by performing at least one of density conversion and filter processing, depending on the type determined by
10 the determining means.

5. An image processing apparatus according to claim 1, wherein the processing means includes:

 changing means for changing the image format of the image data, depending on the type determined by the
15 determining means.

6. An image processing apparatus according to claim 1, wherein the processing means includes:

 processing means for selecting an application of image processing, depending on the type determined by
20 the determining means, setting a parameter, and starting this application to perform image processing of the image data.

7. An image processing apparatus according to claim 1, wherein the processing means includes:

25 means for performing specified processing on the basis of the attribute of the region discriminated by the discriminating means, on the image data in every

region, when the determining result by the determining means is a specified result.

8. An image processing apparatus according to claim 1, wherein the processing means includes:

5 second discriminating means for discriminating the image type of the image data received from the input means in pixel unit, when the determining result by the determining means is a specified result; and

10 second processing means for processing the image data as specified, on the basis of the result discriminated by the second discriminating means.

9. An image processing apparatus according to claim 1, wherein the processing means includes:

15 setting means for setting for pixel unit discriminating process on the basis of the determining result by the determining means;

20 second discriminating means for discriminating the image type of the image data received from the input means in pixel unit on the basis of the setting by the setting means, when the determining result by the determining means is a specified result; and

25 second processing means for processing the image data as specified, on the basis of the result discriminated by the second discriminating means.

10. An image processing apparatus according to claim 1, wherein the processing means includes:

 second discriminating means for discriminating the

image type of the image data received from the input means in pixel unit, when the determining means determines that it takes more than a specified time for determining; and

5 second processing means for processing the image data as specified, on the basis of the result discriminated by the second discriminating means.

11. An image processing apparatus according to claim 1, wherein the processing means includes:

10 second discriminating means for determining the discrimination precision of the discriminating means, and when this discrimination precision is below a specific value, discriminating the image type of the image data received from the input means in pixel unit;
15 and

 second processing means for processing the image data as specified, on the basis of the result discriminated by the second discriminating means.

12. An image processing apparatus according to claim 1, wherein the processing means includes:

20 second discriminating means for determining the complicatedness of the discriminating means, and when this complicatedness is above a specific value, discriminating the image type of the image data
25 received from the input means in pixel unit; and

 second processing means for processing the image data as specified, on the basis of the result

discriminated by the second discriminating means.

13. An image processing apparatus according to claim 1, further comprising:

5 storing means for receiving the image data from the input means, performing a first process on the image data parallel to the determining process of the determining means to obtain a first result, further performing a second process different from the first process to obtain a second result, and storing them in
10 a memory region; and

means for reading out and outputting either one of the first result and second result from the storing means on the basis of the determining result of the determining means.

15 14. An image processing apparatus according to claim 1, wherein the discriminating means and judging means include:

means for discriminating the structure of the background from the extracted region, and judging the
20 type of the image data on the basis thereof.

15 15. An image processing apparatus according to claim 1, wherein the judging means includes:

means for judging presence or absence of character from the distribution of attribute in each region
25 discriminated by the discriminating means, and judging the type of the image data on the basis thereof.

16. An image processing apparatus according to

claim 1, wherein the judging means and processing means include:

judging means for judging the rectangle information and the type of the image data on the basis of the distribution of the attribute in each region discriminated by the discriminating means; and

processing means for processing the data as specified on the basis of the rectangle information and the type of the image data judged by the judging means.

17. An image processing apparatus according to claim 1, wherein the determining means includes:

means for discriminating the page information which is the image type of each page of the original image of the image data when the discriminating means cannot divide the image data into a plurality of rectangular regions, and determining the type of the image data on the basis thereof.

18. An image processing apparatus according to claim 1, wherein the determining means includes:

means for discriminating the page information which is the image type of each page of the original image of the image data when the region extracted by the discriminating means has a complicatedness more than a specific value, and determining the type of the image data on the basis thereof.

19. An image processing apparatus according to claim 1, wherein the judging means includes:

judging means for judging the type of the image data, regardless of the content of the original mode given from the user, on the basis of the distribution of the attribute of each region discriminated by the discriminating means.

20. An image processing apparatus according to claim 1, wherein the processing means includes:

second discriminating means for discriminating the image information of the image data received from the input means in the pixel unit according to the judging result when the judging result by the judging means is the specified result; and

second processing means for processing the image data as specified on the basis of the discrimination result discriminated by the second discriminating means.

21. An image forming apparatus comprising:

input means for inputting image data of an original image;

discriminating means for extracting a predetermined region by using a feature of pixel of the image data input from the input means, and for discriminating an attribute of the region;

determining means for determining the type of the image data on the basis of the distribution of the regions attribute of which discriminated by the discriminating means;

processing means for processing the image data as

specified depending on the type of the image data determined by the determining means; and

image forming means for forming an image on a recording medium on the basis of the image data
5 processed as specified by the processing means.

22. An image processing method comprising:

input step of inputting image data of an original image;

discriminating step of extracting a predetermined
10 region by using a feature of pixel of the image data input at the input step, and for discriminating an attribute of the region;

determining step of determining the type of the image data on the basis of the distribution of the
15 attributes of the regions discriminated at the discriminating step; and

processing step of processing the image data as specified depending on the type of the image data determined at the determining step.

20 23. An image processing method according to claim 22, wherein the determining step includes:

step of determining the type of the image data as at least one type selected from the group consisting of image data of uniform background, image data of dot
25 background in the entire screen, image data of dot photo only, image data of continuous gradation photo only, image data of which region can be discriminated

by rectangle, and image data of which region cannot be discriminated by rectangle.

24. An image processing method according to claim 22, wherein the processing step includes:

5 step of converting at least one of resolution, compression rate, and number of colors of the image data, depending on the type determined at the determining step.

25. An image processing method according to claim 22, wherein the processing step includes:

10 correcting step of correcting the image data by performing at least one of density conversion and filter processing, depending on the type determined at the determining step.

15 26. An image processing method according to claim 22, wherein the processing step includes:

 changing step of changing the image format of the image data, depending on the type determined at the determining step.

20 27. An image processing method according to claim 22, wherein the processing step includes:

 processing step of selecting an application of image processing, depending on the type determined at the determining step, setting a parameter, and starting
25 this application to perform image processing of the image data.

28. An image processing method according to

claim 22, wherein the processing step includes:

step of performing specified processing on the basis of the attribute of the region discriminated at the discriminating step, on the image data in every
5 region, when the determining result at the determining step is a specified result.

29. An image processing method according to claim 22, wherein the processing step includes:

second discriminating step of discriminating the
10 image type of the image data received from the input step in pixel unit, when the determining result at the determining step is a specified result; and

second processing step of processing the image data as specified, on the basis of the result
15 discriminated at the second discriminating step.

30. An image processing method according to claim 22, wherein the processing step includes:

setting step of setting for pixel unit discriminating process on the basis of the determining
20 result at the determining step;

second discriminating step of discriminating the image type of the image data received from the input step in pixel unit on the basis of the setting at the setting step, when the determining result at the
25 determining step is a specified result; and

second processing step of processing the image data as specified, on the basis of the result

discriminated at the second discriminating step.

31. An image processing method according to claim 22, wherein the processing step includes:

second discriminating step of discriminating the
5 image type of the image data received from the input
step in pixel unit, when it is determined that it takes
more than a specified time for determining at the
determining step; and

second processing step of processing the image
10 data as specified, on the basis of the result
discriminated at the second discriminating step.

32. An image processing method according to claim 22, wherein the processing step includes:

second discriminating step of determining the
15 discrimination precision at the discriminating step,
and when this discrimination precision is below a
specific value, discriminating the image type of the
image data received from the input step in pixel unit;
and

20 second processing step of processing the image
data as specified, on the basis of the result
discriminated at the second discriminating step.

33. An image processing method according to claim 22, wherein the processing step includes:

25 second discriminating step of determining the
complicatedness at the discriminating step, and when
this complicatedness is above a specific value,

discriminating the image type of the image data
received from the input step in pixel unit; and

second processing step of processing the image
data as specified, on the basis of the result
5 discriminated at the second discriminating step.

34. An image processing method according to
claim 22, further comprising:

storing step of receiving the image data from the
input step, performing a first process on the image
10 data parallel to the determining process at the
determining step to obtain a first result, further
performing a second process different from the first
process to obtain a second result, and storing them in
a memory region; and

15 step of reading out and outputting either one of
the first result and second result stored at the
storing step on the basis of the determining result at
the determining step.

35. An image processing method according to
20 claim 22, wherein the discriminating step and judging
step include:

step of discriminating the structure of the
background from the extracted region, and judging the
type of the image data on the basis thereof.

25 36. An image processing method according to
claim 22, wherein the judging step includes:

step of judging presence or absence of character

from the distribution of attribute in each region discriminated at the discriminating step, and judging the type of the image data on the basis thereof.

37. An image processing method according to
5 claim 22, wherein the judging step and processing step include the steps of:

judging the rectangle information and the type of the image data on the basis of the distribution of the attribute in each region discriminated at the
10 discriminating step; and

processing the data as specified on the basis of the rectangle information and the type of the image data judged at the judging step.

38. An image processing method according to
15 claim 22, wherein the determining step includes:

step of discriminating the page information which is the image type of each page of the original image of the image data when the discriminating step cannot divide the image data into a plurality of rectangular
20 regions, and determining the type of the image data on the basis thereof.

39. An image processing method according to claim 22, wherein the determining step includes:

step of discriminating the page information which
25 is the image type of each page of the original image of the image data when the region extracted at the discriminating step has a complicatedness more than a

specific value, and determining the type of the image data on the basis thereof.

40. An image processing method according to claim 22, wherein the judging step includes a judging
5 step of judging the type of the image data, regardless of the content of the original mode given from the user, on the basis of the distribution of the attribute of each region discriminated at the discriminating step.

41. An image processing method according to
10 claim 22, wherein the processing step includes:
second discriminating step of discriminating the image information of the image data received from the input means in the pixel unit according to the judging result when the judging result at the judging step is
15 the specified result; and

second processing step of processing the image data as specified on the basis of the discrimination result discriminated at the second discriminating step.

ABSTRACT OF THE DISCLOSURE

The present invention presents an image processing apparatus having an input unit for inputting image data of an original image, a discriminating unit for
5 extracting a predetermined region by using a feature of pixel of the input image data, and for discriminating an attribute of the region, a determining unit for determining the type of the image data on the basis of the distribution of the attributes of the regions, and
10 a processing unit for processing the image data as specified depending on the type of the determined image data. In this constitution, image processing conforming to the accurate discrimination result can be applied to image data.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG.17




FIG. 18

0	1	0
1	-4	1
0	1	0

FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27

PAGE DISCRIMINATION INFORMATION
0. REGION DISCRIMINATION
1. UNIFORM BACKGROUND
2. DOT BACKGROUND
3. DOT PHOTO
4. CONTINUOUS PHOTO
5. INDISCRIMINATIVE
6. TIME OVER

FIG. 28A

ORIGINAL MODE
0. CHARACTER/PHOTO
1. CHARACTER
2. MAP
3. PRINTED PHOTO
4. PHOTOGRAPHIC PRINTING PAPER PHOTO

FIG. 28B

ORIGINAL MODE
AUTOMATIC MODE
CHARACTER/PHOTO MODE
CHARACTER MODE
MAP MODE
PRINTED PHOTO MODE
PHOTOGRAPHIC PRINTING
PAPER PHOTO MODE

FIG. 28C

PAGE DISCRIMINATION INFORMATION
0. UNIFORM BACKGROUND
1. DOT BACKGROUND
2. DOT PHOTO
3. CONTINUOUS PHOTO

FIG. 28D




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35

PAGE DISCRIMINATION RESULT	PAGE DIS-CRIMINATION CODE	REGION DIS-CRIMINATION CODE	COLOR CONVERSION	BACKGROUND PROCESSING	PIXEL DISCRIMINATION	FILTER	BLACK COLOR/BLACK CHARACTER	GRADATION PROCESSING
UNIFORM BACKGROUND	0	0	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO A	CHARACTER/PHOTO A	CHARACTER/PHOTO	CHARACTER/PHOTO
DOT BACKGROUND		1			CHARACTER/PHOTO B	CHARACTER/PHOTO B		
DOT PHOTO		2			-	CHARACTER/PHOTO C		
CONTINUOUS PHOTO		3			-	CHARACTER/PHOTO D		
UNIFORM BACKGROUND	1	-	CHARACTER	CHARACTER	CHARACTER/PHOTO A	CHARACTER/PHOTO A	CHARACTER	CHARACTER
DOT BACKGROUND	2	-	MAP	MAP	CHARACTER/PHOTO B	CHARACTER/PHOTO B	MAP	MAP
DOT PHOTO	3	-	PRINTED PHOTO	PRINTED PHOTO	-	PRINTED/PHOTO	PRINTED PHOTO	PRINTED PHOTO
CONTINUOUS PHOTO	4	-	PHOTOGRAPHIC PRINTING PAPER PHOTO	PHOTOGRAPHIC PRINTING PAPER PHOTO	-	PHOTOGRAPHIC PRINTING PAPER PHOTO	PHOTOGRAPHIC PRINTING PAPER PHOTO	PHOTOGRAPHIC PRINTING PAPER PHOTO
INDISCRIMINATIVE	5	-	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO
OTHERS	6	-	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO	CHARACTER/PHOTO

FIG. 36

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I HEREBY DECLARE:

THAT my residence, post office address, and citizenship are as stated below next to my name;

THAT I believe I am the original, first, and sole inventor (if only one inventor is named below) or an original, first, and joint inventor (if plural inventors are named below or in an attached Declaration) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**IMAGE PROCESSING APPARATUS, IMAGE FORMING APPARATUS, AND IMAGE
PROCESSING METHOD DEPENDING ON THE TYPE OF ORIGINAL IMAGE**

(Attorney Docket No. 016907/1080)

the specification of which (check one)

 is attached hereto.

 X was filed on March 17, 2000 as United States Application
Number or PCT International Application Number
and was amended on _____
(if applicable).

THAT I do not know and do not believe that the same invention was ever known or used by others in the United States of America, or was patented or described in any printed publication in any country, before I (we) invented it;

THAT I do not know and do not believe that the same invention was patented or described in any printed publication in any country, or in public use or on sale in the United States of America, for more than one year prior to the filing date of this United States application;

THAT I do not know and do not believe that the same invention was first patented or made the subject of an inventor's certificate that issued in any country foreign to the United States of America before the filing date of this United States application if the foreign application was filed by me (us), or by my (our) legal representatives or assigns, more than twelve months (six months for design patents) prior to the filing date of this United States application;

THAT I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment specifically referred to above;

THAT I believe that the above-identified specification contains a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the invention, and sets forth the best mode contemplated by me of carrying out the invention; and

THAT I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I HEREBY CLAIM foreign priority benefits under Title 35, United States Code § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number	Country	Foreign Filing Date	Priority Claimed?	Certified Copy Attached?
11-094981	Japan	1 April 1999	Yes	
11-094982	Japan	1 April 1999	Yes	

I HEREBY CLAIM the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

U.S. Provisional Application Number	Filing Date

I HEREBY CLAIM the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application Number	PCT Parent Application Number	Parent Filing Date	Parent Patent Number

I HEREBY APPOINT the following registered attorneys and agents of the law firm of FOLEY & LARDNER to have full power to prosecute this application and any continuations, divisions, reissues, and reexaminations thereof, to receive the patent, and to transact all business in the United States Patent and Trademark Office connected therewith:

STEPHEN A. BENT	Reg. No. 29,768
DAVID A. BLUMENTHAL	Reg. No. 26,257
BETH A. BURROUS	Reg. No. 35,087
ALAN I. CANTOR	Reg. No. 28,163
WILLIAM T. ELLIS	Reg. No. 26,874
JOHN J. FELDHAUS	Reg. No. 28,822
PATRICIA D. GRANADOS	Reg. No. 33,683

JOHN P. ISACSON	Reg. No. 33,715
MICHAEL D. KAMINSKI	Reg. No. 32,904
LYLE K. KIMMS	Reg. No. 34,079
KENNETH E. KROSIN	Reg. No. 25,735
JOHNNY A. KUMAR	Reg. No. 34,649
GLENN LAW	Reg. No. 34,371
PETER G. MACK	Reg. No. 26,001
BRIAN J. MC NAMARA	Reg. No. 32,789
SYBIL MELOY	Reg. No. 22,749
RICHARD C. PEET	Reg. No. 35,792
GEORGE E. QUILLIN	Reg. No. 32,792
COLIN G. SANDERCOCK	Reg. No. 31,298
BERNHARD D. SAXE	Reg. No. 28,665
CHARLES F. SCHILL	Reg. No. 27,590
RICHARD L. SCHWAAB	Reg. No. 25,479
ARTHUR SCHWARTZ	Reg. No. 22,115
HAROLD C. WEGNER	Reg. No. 25,258

and I request that all correspondence be directed to:

Richard L. Schwaab
 FOLEY & LARDNER
 Washington Harbour
 3000 K Street, N.W., Suite 500
 P.O. Box 25696
 Washington, D.C. 20007-8696

Telephone: (202) 672-5300
 Facsimile: (202) 672-5399

I UNDERSTAND AND AGREE THAT the foregoing attorneys and agents appointed by me to prosecute this application do not personally represent me or my legal interests, but instead represent the interests of the legal owner(s) of the invention described in this application.

I FURTHER DECLARE THAT all statements made herein of my own knowledge are true, and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Name of first inventor	Naoaki KODAIRA
Residence	Kawasaki-shi, Japan
Citizenship	Japan
Post Office Address	314, Kureare-Toshiba-Miyazakidai, 1-9-12, Miyazaki, Miyamae-ku, Kawasaki-shi, Kanagawa-ken, Japan
Inventor's signature	
Date	

Name of second inventor	Hiroaki KUBOTA
Residence	Kamakura-shi, Japan
Citizenship	Japan
Post Office Address	1933-2, Yamazaki, Kamakura-shi, Kanagawa-ken, Japan
Inventor's signature	
Date	
Name of third inventor	Hiroki KANNO
Residence	Yokohama-shi, Japan
Citizenship	Japan
Post Office Address	1-18-1-B602, Kamiookahigashi, Konan-ku, Yokohama-shi, Kanagawa-ken, Japan
Inventor's signature	
Date	